



## VIDEO ENCODER

### Video Compression

H.264 (MPEG-4 Part 10/AVC)  
Motion JPEG

### Resolutions

176x120 to 720x576

### Frame Rate: H.264

30/25 (NTSC/PAL) fps in all resolutions

### Frame Rate: Motion JPEG

30/25 (NTSC/PAL) fps in all resolutions

### Video Streaming

Multi-stream H.264 and Motion JPEG: 3 simultaneous, individually configured streams in max. resolution at 30/25 fps; more streams if identical or limited in frame rate/resolution

Controllable frame rate and bandwidth

VBR/CBR H.264

### Image Settings

Compression, color, brightness, contrast

Rotation: 90°, 180°, 270°

Aspect ratio correction

Mirroring of images

Text and image overlay

Privacy mask

Enhanced deinterlace filter

### Pan/Tilt/Zoom

Wide range of analog PTZ cameras supported (drivers available for download at [www.axis.com](http://www.axis.com))

100 presets, guard tour, PTZ control queue

Supports Windows compatible joysticks

## NETWORK

### Security

Password protection, IP address filtering, HTTPS encryption, IEEE 802.1X network access control, digest authentication, user access log

### Supported Protocols

IPv4/v6, HTTP, HTTPS, QoS layer 3 DiffServ, FTP, SMTP, Bonjour, UPnP, SNMPv1/v2c/v3(MIB-II), DNS, DynDNS, TP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS

## SYSTEM INTEGRATION

### Application Programming Interface

Open API for software integration, including VAPIX® from AXIS Communications available at [www.axis.com](http://www.axis.com)

AXIS Camera Application Platform from Axis Communications; specifications available at [www.axis.com](http://www.axis.com)

Includes the ONVIF specification available at [www.onvif.org](http://www.onvif.org)  
Support for AXIS Video Hosting System (AVHS) with One-Click Camera Connection

### Intelligent Video

Video motion detection, active tampering alarm, audio detection  
Support for AXIS Camera Application Platform enabling installation of additional applications

### Alarm Triggers

Intelligent video, external inputs, video loss, disk full

### Alarm Events

File upload via FTP, HTTP and email

Notification via email, HTTP and TCP

External output activation

PTZ presets

Local storage

### Video Buffer

64 MB pre- and post-alarm

## GENERAL

### Approvals

EN 55022 Class B, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR22, EN 60950-1